

DIN 14 321, 322, 323, 307, 308, 309
Storz



DIN 14 321, 322, 323, 307, 308, 309 Storz

MATERIAL MATIÈRE MATERIAL

AL = Aluminium

SIZE DIMENSIONS DIMENSIONES


DN 50/80/100 mm

GASKETS JOINTS JUNTA

NBR

THREAD FILETAGE ROSCA




BSPF/NF ISO 228-1



DN	KA
52-C	66
75-B	89
110-A	133


■ AL = Aluminium
 ■ BR = Brass *Laiton Latón*
 ■ ST = Steel *Acier Acero*
 ■ SS = Stainless steel *Inox*
 ■ PP = Polypropylene

Trelleborg Fittings 2013

		ID coupling Diam. raccord Diam. racor	ID shank Diam. douille Diam. espiga	Ref.	Notes	
 <p>Secure female thread. Fileté femelle sécurisé. <i>Rosca hembra securizado.</i></p>	Type C.	52	2"	510 15 37		
	Type B.	AL	75	3"	510 15 38	
	Type A.		110	4"	510 15 39	
 <p>Female thread. Fileté femelle. <i>Rosca hembra.</i></p>	Type C. DIN 14 307.		52	2"	510 17 71	
	Type B. DIN 14 308.	AL	75	3"	510 17 72	
	Type A. DIN 14 309.		110	4"	510 17 73	
 <p>Swivel female thread. Fileté femelle tournant. <i>Rosca hembra giratorio.</i></p>	Type C.		52	2"	510 50 96	
	Type B.	AL	75	3"	510 50 97	
	Type A.		110	4"	510 17 74	

■ AL = Aluminium
 ■ BR = Brass *Laiton Latón*
 ■ ST = Steel *Acier Acero*
 ■ SS = Stainless steel *Inox*
 ■ PP = Polypropylene

Trelleborg Fittings 2013

		ID coupling Diam. raccord Diam. racor	ID shank Diam. douille Diam. espiga	Ref.	Notes
 <p>Serrated hose shank. Cannelé. <i>Acanalado.</i></p>	Type C. DIN 14 321.	52		510 71 25	
	Type B. DIN 14 322.	AL	75		510 18 16
	Type A. DIN 14 323.		110		510 89 91
 <p>Smooth hose shank/ Collar. Douille lisse/Collette. <i>Caña lisa/Cuello.</i></p>	Type C.	52	50	510 50 98	
	Type B.	AL	75	75	510 50 99
	Type A.		110	100	510 51 00
 <p>Cap. Bouchon. <i>Tapon.</i></p>	Type C. DIN 14 311.	52		510 51 01	
	Type B. DIN 14 312.	AL	75		510 18 17
	Type A. DIN 14 313.		110		510 51 02